

3214 WD

REVISIONS

ISSUE	DATE	AUTH. NO.
16	1-26-60	28-12423
17	3-7-60	28-12531
18	3-15-60	28-12912
19	9-16-60	28-13910
20	9-20-60	28-13920
21	10-14-60	28-13541
22	2-20-61	69056
23	4-12-61	69485
24	6-1-61	70011
25	8-3-61	70085
26	11-28-61	71780
27	1-11-62	72128
28	5-2-62	73280
29	9-21-62	74605
30	1-10-63	75678
31	1-21-63	75760
32	3-28-63	76401
33	4-15-63	76591
34	5-2-63	76756
35	5-20-63	76966
36	6-15-63	76147
37	10-30-63	78340
38	11-12-63	78059
39	12-5-63	79091
40	12-13-63	79185
41	12-23-63	79185-1
42	1-9-65	85722
43	2-3-65	85959
	12-1-56 DATE	
	ACTUAL	
	WIRING DIAGRAM FOR	
	MODEL 28, TYPING UNITS	
	LP 14, 15, 16, 17, 20, 21, 23, 26, 27, 28, 30, 31, 34, 38, 39, 43, 44, 53, 56, 60, 65, 67, 68, 70, 73, 84, 96, 101, 108, 111, 113, 122	
	STUNT BOX	
	AP, AR, AS, AW, AX, AY, ACV, ACW, ACX, ACY, ACZ, ADL, AEH, AES, AET, AFD, AFE, AFN, AGB, AGD, AGE, AFY, AGJ, AGG, AHF, AH, AHT, AHV, AYH, AHZ, AJG AJA, AJC, AJD, AJF, AJG, AJB, AJK	
	SEQUENTIAL SELECTOR UNIT	
	LS 2, 4.	
	PD. FILE NO. 45-3065AA	
	DRAWN RAB CK G.G.	
	ENG. V.C. APP. OAL	
	TELETYPE CORPORATION	
	3214 WD	

NO	NOTES
1.	WIRING CHANNEL DESIGNATED BY "C" DOES NOT REPRESENT CABLES, BUT ASSISTS IN TRACING CONNECTIONS.
2.	COLOR LEGEND C - CHANNEL IDENTIFICATION 8 - CHANNEL WIRE NUMBER WIRE COLOR CODE
3.	COLOR CODE: BK - BLACK W - WHITE Y - YELLOW P - PURPLE S - SLATE BL - BLUE R - RED BR - BROWN O - ORANGE G - GREEN
5.	CONNECTOR VIEWED FROM SOLDERED TERMINAL ENDS.
7.	THESE LEADS FURNISHED WITH FUNCTION BOX.
8.	NORMALLY OPEN CONTACT
9.	NORMALLY CLOSED CONTACT
10.	A COMPLETE LP UNIT USES ONLY ONE STUNT BOX. MAKE APPROXIMATE (---) CONNECTIONS TO COMPLETE CIRCUIT.
11.	TRANSFER CONTACTS REAR CONTACTS NORMALLY OPEN REAR CONTACTS NORMALLY CLOSED
12.	THE FOLLOWING STUNT BOXES ARE WITHOUT SWITCH ASSEMBLIES: AX, ADL.
13.	THESE TWO TERMINALS ARE USED WHEN LP IS EQUIPPED WITH XD CONT. PAGE FEED OUT OR XD CONT. HORIZ. TAB. IF BOTH FEATURES ARE USED, THEY ARE WIRED IN SERIES TO THESE TERMINALS.
14.	USE 39522 RM STRAP FOR LP 95, 96, 97, 102, 122.
15.	THE 159611 SIGNAL BELL AND THE 195353 CABLE ASSEMBLY ARE CONTAINED ON THE LPIII ONLY.
16.	A. THE LPIII IS FACTORY WIRED FOR 60MA. OPERATION. B. THE LPIII MAY BE CONVERTED FOR 20-30 MA. OPERATION BY THE CUSTOMER.
17.	FOR AFY STUNT BOX, CONTACT IS OVER SLOT 30.
18.	195269 STRAP CONNECTED FROM TERMINAL 6 TO CONNECTOR BRACKET MOUNTING SCREW FOR 179613 AND 179644 R.F. SUPPRESSION MODIFICATION KITS.

